

SAFETY DATA SHEET

Section 1.	Identification of the material and the supplier
------------	---

<p>Product:</p> <p>Item Code:</p> <p>Product Use:</p> <p>Restriction of Use:</p> <p>Australian Supplier:</p> <p>Address:</p> <p>Telephone:</p> <p>Email:</p> <p style="color: red;">New Zealand Supplier:</p> <p style="color: red;">Address:</p> <p style="color: red;">Telephone:</p> <p>Emergency Numbers:</p> <p>Australia:</p> <p>New Zealand:</p> <p>Date of SDS Preparation:</p>	<p>Weatherfast Premium Satin White</p> <p>8402</p> <p>High gloss water resistant paint for severe exposure conditions. Applied by brush, roller or spray</p> <p>Refer to Section 15</p> <p>Norglass Paints</p> <p>59 Moxon Road</p> <p>Punchbowl NSW 2196</p> <p>Australia</p> <p>+61 2 9708 2200</p> <p>info@norglass.com.au</p> <p style="color: red;">xxx</p> <p style="color: red;">xxx</p> <p style="color: red;">xxx</p> <p style="color: red;">0508 724687</p> <p>13 1126 (Poisons Information Centre)</p> <p>0800 764 766 (National Poison Centre)</p> <p>12 August 2021</p>
---	--

Section 2.	Hazards Identification
------------	------------------------

Australia:
Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:
This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (Flammable, Carcinogenic) – HSR002669

Pictograms



Flammable Toxic/Irritant Chronic Ecotoxic

Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.

Skin irritation Cat. 2	H315	Causes skin irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Carcinogenicity Cat. 2	H351	Suspected of causing cancer.
Reproductive toxicity Cat. 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Urethane Alky Resin	50 - 69	Proprietary
White Spirits	10 - 15	64742-88-7
Pigments various	5-20	Proprietary
Additives	Up to 100	Proprietary

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	May be fatal if swallowed and enters airways.
Inhalation:	Not applicable.
Skin:	Causes skin irritation. May cause an allergic skin reaction.
Eyes:	Causes damage to eyes.
Chronic:	Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Liquid
Hazards from combustion products	Oxides of carbon, possible toxic fumes
Suitable Extinguishing media	Extinguishing media carbon dioxide foam or dry chemicals.
Precautions for firefighters and special protective clothing	Wear full protective gear.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations. Adequate steps should be taken to prevent spillage reaching waterways and drains.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting.

- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Keep out of reach of children.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³

No ingredients have exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2020 12TH EDITION.

Engineering Controls

Use only in well ventilated areas. Introduce local exhaust ventilation if necessary.

Personal Protection

Eyes	Wear safety goggles.
Hands and Skin	Wear neoprene rubber gloves. Wear overalls and use barrier cream.
Respiratory	Avoid breathing vapour of dust by wearing organic vapour respirators.

Section 9 Physical and Chemical Properties

Appearance	Coloured viscous liquid
Odour	Low solvent
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	150°C for solvent
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	32°C
Flammability	Not applicable
Upper and Lower Exposure Limits	Not applicable
Volatile Component	20-25
Vapour Density	Not applicable
Specific Gravity	0.930 – 1.180
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable

Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	None known.
Hazardous Decomposition Products	Oxides of carbon, possible toxic fumes

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell Mutagenicity	Not applicable.
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Causes damage to organs through prolonged or repeated exposure.

Section 12. Ecotoxicological Information

Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic" along with appropriate pictograms from section 2, waste identifier, and business name, address, and phone number. If triple rinsing container, add rinsate to waste container for disposal.

Disposal methods to avoid: Do not allow to enter waterways.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)



Road and Rail Transport

UN No: 1263
Class-primary 3
Packing Group III
Sub Class 9
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

Air Transport

UN No: 1263
Class-primary 3
Packing Group III
Sub Class 9
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

Marine Transport

UN No: 1263
Class-primary 3
Packing Group III
Sub Class 9
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

Limited Quantities Statement:

If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Not classified as a Schedule 5 Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (Flammable, Carcinogenic) – HSR002669

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Fire Extinguisher Quantities	500L – 2x required
Signage Trigger Quantities	1000L (Hazardous to the aquatic environment chronic Cat. 2)
Emergency Response Plan	1000L (Hazardous to the aquatic environment chronic Cat. 2)
Secondary Containment	1000L (Hazardous to the aquatic environment chronic Cat. 2)
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information

Product Name: Weatherfast Premium Satin White
Date of SDS: 12 August 2021

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Glossary

Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
3. Standard for the Uniform Scheduling of Medicines and Poisons.
4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
6. Workplace exposure standards for airborne contaminants, Safe work Australia.
7. American Conference of Industrial Hygienists (ACGIH).
8. Globally Harmonised System of Classification and Labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 12 August 2021 Review Date: 12 August 2026