

## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: **Norseal Epoxy Wood Treatment - Base**  
 Item Code: 1202  
 Product Use: Epoxy Wood Treatment 2 pack  
 Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**  
 Address: 59 Moxon Road  
 Punchbowl NSW 2196  
 Australia  
 Telephone: +61 2 9708 2200  
 Email: [info@norglass.com.au](mailto:info@norglass.com.au)

New Zealand Supplier: xxx  
 Address: xxx  
 Telephone: 0508 724687

**Emergency Numbers:**  
**Australia: 13 1126 (Poisons Information Centre)**  
**New Zealand: 0800 764 766 (National Poison Centre)**

Date of SDS Preparation: 15 November 2023

### Section 2. Hazards Identification

**Australia:**  
 Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

**New Zealand:**  
 This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

**EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662**

#### Pictograms



Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.

Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Reproductive toxicity Cat. 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.
Hazardous to terrestrial vertebrates	H433	Hazardous to terrestrial vertebrates

<b>Prevention Code</b>	<b>Prevention Statement</b>
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.

<b>Response Code</b>	<b>Response Statement</b>
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

<b>Storage Code</b>	<b>Storage Statement</b>
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

<b>Disposal Code</b>	<b>Disposal Statement</b>
P501	Dispose of according to Local Regulations or Authorities

### **Section 3. Composition / Information on Ingredients**

<b>Ingredients</b>	<b>Wt%</b>	<b>CAS NUMBER.</b>
Epoxy Resin	55-65	25068-38-6
Xylene	20-30	1330-20-7
MEK	10-15	78-93-3
Pine Oil	1-5	8002-09-03

### **Section 4. First Aid Measures**

## Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

## Most important symptoms and effects, both acute and delayed

### Symptoms:

<b>Ingestion:</b>	May be harmful if swallowed. Aromatic solvents may irritate mouth, throat and digestive tract.
<b>Inhalation:</b>	Cause respiratory irritation.
<b>Skin:</b>	May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. May cause defatting.
<b>Eye:</b>	Causes serious eye irritation.
<b>Chronic:</b>	May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child.

## Section 5. Fire Fighting Measures

<b>Hazard Type</b>	Flammable Liquid
<b>Hazards from combustion products</b>	Hazardous Products: Carbon monoxide Carbon dioxide
<b>Suitable Extinguishing media</b>	Extinguishing media carbon dioxide, foam or dry chemicals.
<b>Precautions for firefighters and special protective clothing</b>	Wear full body protection and self-contained breathing apparatus. Water may be used to cool down the fire exposed containers. Keep heat and naked flame away from spill
<b>HAZCHEM CODE</b>	<b>3Y</b>

## Section 6. Accidental Release Measures

### Personal precautions:

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

### Environmental precautions:

Adequate steps should be taken to prevent spillage reaching waterways and drains.

### Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

## Section 7. Handling and Storage

Product Name: Norseal Wood Treatment - Base  
Date of SDS: 15 November 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: 64 9 475 5240 www.techcomp.co.nz

### Precautions for Handling:

- Read carefully and follow all instructions.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective clothing and equipment.

### Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Keep out of reach of children.

## Section 8 Exposure Controls / Personal Protection

### WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Xylene	[1330-20-7]	50	217	-	-
Methyl ethyl ketone, MEK	[78-93-3]	150	445	300	890

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

### Engineering Controls

Use only in well ventilated areas. Introduce local exhaust ventilation if necessary.

### Personal Protection Equipment



<b>Eyes</b>	Wear safety goggles with side shields.
<b>Hands and Skin</b>	Wear chemical resistant rubber gloves. Wear overalls and use barrier cream.
<b>Respiratory</b>	Avoid breathing dust arising from sanding the product or solvent vapours by wearing organic vapour respirators.

## Section 9 Physical and Chemical Properties

<b>Appearance</b>	Clear viscous liquid
<b>Odour</b>	Strong solvent odour
<b>Odour Threshold</b>	Not applicable
<b>pH</b>	Not applicable
<b>Boiling Point</b>	137-143°C for solvent
<b>Melting Point</b>	Not applicable
<b>Freezing Point</b>	Not applicable
<b>Flash Point</b>	27°C(cup closed)

Product Name: Norseal Wood Treatment - Base  
Date of SDS: 15 November 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: 64 9 475 5240 www.techcomp.co.nz

<b>Flammability</b>	Not applicable
<b>Upper and Lower Exposure Limits</b>	1.1 – 7.7(solvents)
<b>Volatile Component</b>	40% by volume
<b>Vapour Pressure 25°C</b>	5.2 kpa at 38°C for xylene
<b>Specific Gravity</b>	1.060
<b>Solubilities</b>	Immiscible
<b>Partition Coefficient:</b>	Not applicable
<b>Auto-ignition Temperature</b>	Not applicable
<b>Decomposition Temperature</b>	Not applicable
<b>Kinematic Viscosity</b>	Not applicable
<b>Particle Characteristics</b>	Not applicable

### Section 10. Stability and Reactivity

<b>Stability of Substance</b>	This product is stable under normal conditions.
<b>Conditions to Avoid</b>	Sources of ignition. Heat.
<b>Incompatible Materials</b>	Incompatible with Halogens and oxidising agents.
<b>Hazardous Decomposition Products</b>	Hazardous Products: Carbon monoxide Carbon dioxide

### Section 11 Toxicological Information

#### Acute Effects:

<b>Swallowed</b>	Not applicable.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not applicable.
<b>Eye</b>	Causes serious eye irritation.
<b>Skin</b>	Causes skin irritation. May cause an allergic skin reaction.

#### Chronic Effects:

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	May be fatal if swallowed and enters airways.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Causes damage to organs through prolonged or repeated exposure.

#### Individual component information:

##### Acute Toxicity:

<b>Chemical Name</b>	<b>Oral – LD50</b>	<b>Dermal – LD50</b>	<b>Inhalation – LC50</b>
Xylene (1330-20-7)	1590 mg/kg (mouse)	-	>27.6mg/L(Rat) Vapour
MEK (78-93-3)	2737mg/kg (Rat)	-	-

### Section 12. Ecotoxicological Information

Toxic to aquatic life with long lasting effects.  
Hazardous to terrestrial vertebrates.

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available

<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	No data available
<b>Precautions</b>	<b>Do not allow to enter waterways.</b>

**Individual component information (Please refer to [www.epa.govt.co.nz](http://www.epa.govt.co.nz) for full details):**

**Xylene (1330-20-7):**

Route	Species	Duration	Value LC50/EC50
Fish	Oncorhynchus mykiss Rainbow trout, donaldson trout	96 hr (static)	3.3 mg/L
Crustacean	Palaemonetes pugio (Crustacea)	48 hr	8.5mg/L
Algal	Skeletonema costatum (Algae)	72hr (static)	10mg/L
Bioaccumulative	No		
Rapidly Degradable	Yes		

**Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6):**

Route	Species	Duration	Value LC50/EC50
Fish	-	28 days	<10 mg/L
Crustacean	-	28 days	<10 mg/L
Bioaccumulative	ND		
Rapidly Degradable	No		

**Section 13. Disposal Considerations**

**Disposal Method:** Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

**Precautions:** Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

**Disposal methods to avoid:** Do not allow to enter waterways.

**Section 14 Transport Information**

**This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).**

**This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020**



<b>UN No</b>	1866
<b>Class - Primary</b>	3
<b>Packing Group</b>	III
<b>Proper Shipping Name</b>	RESIN SOLUTION, FLAMMABLE LIQUID
<b>Marine Pollutant</b>	YES
<b>Special Provisions</b>	If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

**Section 15 Regulatory Information**

**Australia:**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### **New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Surface Coatings and Colourants (Flammable) – HSR002662

<b>HSW (HS) Regulations 2017 and EPA Notices</b>	<b>Trigger Quantity</b>
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	Only use for the intended purpose.

### **Section 16 Other Information**

#### **Glossary**

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

#### **References:**

##### **Australia:**

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

##### **New Zealand:**

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

#### **Disclaimer**

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to

TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 15 November 2023

Review Date: 15 November 2028