

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **WEATHERFAST A1 PENETRATING OIL**
 Item Code:
 Product Use: Penetrating Oil
 Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**
 Address: 59 Moxon Road
 Punchbowl NSW 2196
 Australia
 Telephone: +61 2 9708 2200
 Email: info@norglass.com.au

New Zealand Supplier: xxx
 Address: xxx
 Telephone: 0508 724687

Emergency Numbers:
Australia: 13 1126 (Poisons Information Centre)
New Zealand: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 7 March 2023

Section 2. Hazards Identification

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Lubricants (Flammable) – HSR002603
 Metal Industry Products (Flammable) – HSR002611

Pictograms



Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.

Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Germ cell mutagenicity Cat. 2	H341	Suspected of causing genetic defects.
Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 3	H412	Harmful to aquatic life with long lasting effects.

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P260	Do not breathe fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use foam, water fog, dry chemical, or CO ² to extinguish.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated heavy	65-70	64742-48-9

Eterkyd 1107	10-15	Mixture consisting of: 8030-30-6 1330-20-7
Naphtha (petroleum), hydrosulfurized heavy; low boiling point hydrogen treated naphtha	5-10	64742-82-1
Polyphases AF3	1-3	Mixture including: 55406-53-6
Methyl ethyl ketoxime	0.1-0.5	96-29-7
Cobalt compound	0.1-0.5	Mixture consisting of: 64742-81-0 136-52-7 91-20-3
Ingredients determined not to be hazardous or triggering final classification	To bal	

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Immediately call a POISON CENTER or doctor/physician.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	May be fatal if swallowed and enters airways.
Inhalation:	May cause drowsiness or dizziness.
Skin:	Causes skin irritation. May cause an allergic skin reaction.
Eyes:	Causes serious eye irritation.
Chronic:	Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Liquid or vapour.
Hazards from combustion products	Carbon monoxide, carbon dioxide.
Suitable Extinguishing media	Use foam, water fog, dry chemical, or CO ₂ . Do not use straight streams of water.
Precautions for firefighters and special protective clothing	Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA). This product should be prevented from entering drains and watercourses.

Product Name: Weatherfast A1 Penetrating Oil
Date of SDS: 7 March 2023

SDS Prepared by: Technical Compliance Consultants
Tel: 64 9 475 5240 www.techcomp.co.nz

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel. Extinguish or remove all sources of ignition and stop leak if safe to do so. Evacuate all unprotected personnel.

Prevent spillage from entering drains or water courses.

Contain any spilled liquid with sand or earth. Use clean non-sparking tools to collect absorbed material. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces. Dispose of waste according to the applicable local and national regulations detailed in Section 13

Section 7. Handling and Storage**Precautions for Handling:**

- Keep out of reach of children.
- Read carefully and follow all instructions.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid contact with skin and eyes.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Ground and bond container and receiving equipment.
- Use explosion-proof [electrical, ventilating and lighting] equipment
- Use non-sparking tools.
- Take action to prevent static discharge.
- Do not breathe fumes, vapours or spray.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.
- Use personal protective equipment as required.

Precautions for Storage:

- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Store in the original container.
- Keep container tightly closed.

Section 8 Exposure Controls / Personal Protection**WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Naphthalene	[91-20-3]	0.5	2.6	2	10
Xylene (o-, m-, p-isomers)	[1330-20-7]	50	217	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

Personal Protection Equipment:



Eyes	Safety glasses with side shields. Avoid wearing contact lenses.
Hands	Wear chemical resistant gloves. Recommended material: Nitrile
Body	Chemical/oil resistant clothing is recommended.
Respiratory	Type A filter material (organic vapour) Refer to AS/NZS 1715: Selection, Use and Maintenance of Respiratory Equipment and AS/NZS 1716: Respiratory Protective Devices for further details on the use of respiratory protective equipment.

Section 9 Physical and Chemical Properties

Appearance	Liquid
Colour	Amber
Odour	Solvent
Odour Threshold	Not available
pH	Not available
Boiling Point	150°C for solvent
Melting Point	Not available
Freezing Point	Not available
Flash Point	32°C
Flammability	Flammable liquid or vapour
Lower to upper Flammable Limits	Not available
Volatile Component	Not available
Relative Vapour Density	Not available
Specific Gravity	0.844
Solubilities	Not available
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Kinematic Viscosity	Not available
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, open flames, direct sunlight and other sources of ignition.
Incompatible Materials	Strong oxidisers. Other flammable materials
Hazardous Decomposition Products	No data available.

Section 11 Toxicological Information

Acute Effects:

Swallowed	May be fatal if swallowed and enters airways.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes serious eye irritation.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Suspected of causing genetic defects.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

Section 12. Ecotoxicological Information

Harmful to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable" and that the label also has the Flammable Pictogram, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: Avoid release to the environment.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)



Road, Rail, Sea and Air Transport

UN No	1993
Class - Primary	3
Packing Group	III
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Marine Pollutant	Yes
Special Provisions	If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Schedule 6 Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Fire Extinguisher Quantities	500L – 2x required
Signage Trigger Quantities	1000L
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	Only use for the intended purpose.

Section 16	Other Information
-------------------	--------------------------

Glossary

Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:**Australia:**

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
3. Standard for the Uniform Scheduling of Medicines and Poisons.
4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
6. Workplace exposure standards for airborne contaminants, Safe work Australia.
7. American Conference of Industrial Hygienists (ACGIH).
8. Globally Harmonised System of Classification and Labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 7 March 2023 Review Date: 7 March 2028