

SAFETY DATA SHEET

Section 1. Id	entification of the material and the supplier
Product:	WEATHERFAST A2 FINISHING OIL
Item Code: Product Use:	Finishing Oil
Restriction of Use:	Refer to Section 15
Australian Supplier: Address:	Norglass Paints 59 Moxon Road
	Punchbowl NSW 2196 Australia
Telephone:	+61 2 9708 2200
Email:	info@norglass.com.au
New Zealand Supplier: Address:	XXX XXX
Telephone:	xxx 0508 724687
Emergency Numbers	
Australia: New Zealand:	13 1126 (Poisons Information Centre) 0800 764 766 (National Poison Centre)
Date of SDS Preparation	n: 7 March 2023
Section 2. Ha	azards Identification
Australia:	

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662

Pictograms



Signal Word: DANGER

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.

SDS Prepared by: Technical Compliance Consultants Tel: 64 9 475 5240 www.techcomp.co.nz

Germ cell mutagenicity Cat. 2	H341	Suspected of causing genetic defects.
Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical, ventilating and lighting] equipment
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P260	Do not breathe fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use foam, water fog, dry chemical, or CO ² to extinguish.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement	
P501	Dispose of according to Local Regulations or Authorities	

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated	25-30	64742-48-9
heavy		
Naphtha (petroleum),	20-25	64742-82-1
hydrodesulfurized heavy; low boiling		
point hydrogen treated naphtha		
Dreduct Names Westherfast A2 Einishing Oil CDC Drenard by: Tashnisal Compliance		Technical Compliance Consultant

Product Name: Weatherfast A2 Finishing Oil Date of SDS: 7 March 2023

SDS Prepared by: Technical Compliance Consultants Tel: 64 9 475 5240 www.techcomp.co.nz

Setal 3275	20-25	Mixture consisting of: 64742-82-1 64742-95-6 1330-20-7 100-41-4
Eterkyd 1107	10-15	Mixture consisting of: 8030-30-6 1330-20-7
Polyphases AF3	1-3	Mixture including: 55406-53-6
Methyl ethyl ketoxime	0.5 - 1	96-29-7
Cobalt compound	0.1-0.5	Mixture consisting of: 64742-81-0 136-52-7 91-20-3
Ingredients determined not to be hazardous or not triggering final classification	To bal	

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Immediately call a POISON CENTER or doctor/physician.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.
Most important sy Symptoms:	mptoms and effects, both acute and delayed
Ingestion:	May be fatal if swallowed and enters airways.
Inhalation:	May cause drowsiness or dizziness.
Skin:	Causes skin irritation. May cause an allergic skin reaction.
Eves:	Causes serious eve irritation.

Eyes:	Causes serious eye irritation.
Chronic:	Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

Fire Fighting Measures

Hazard Type	Flammable Liquid or vapour.	
Hazards from	Carbon monoxide, carbon dioxide.	
combustion		
products		
Suitable	Use foam, water fog, dry chemical, or CO ₂ . Do not use straight streams	
Extinguishing	of water.	
media		
Precautions for	Fire fighters should wear full protective clothing and self-contained	
firefighters and	breathing apparatus (SCBA). This product should be prevented from	
Product Name: Weatherfast A2 Finishing Oil SDS Prepared by: Technical Compliance Consultant		

Section 5.

special protective clothing	entering drains and watercourses.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel. Extinguish or remove all sources of ignition and stop leak if safe to do so. Evacuate all unprotected personnel.

Prevent spillage from entering drains or water courses.

Contain any spilled liquid with sand or earth. Use clean non-sparking tools to collect absorbed material. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces. Dispose of waste according to the applicable local and national regulations detailed in Section 13

Section 7. Handling and Storage

Precautions for Handling:

- Keep out of reach of children.
- Read carefully and follow all instructions.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid contact with skin and eyes.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Ground and bond container and receiving equipment.
- Use explosion-proof [electrical, ventilating and lighting] equipment
- Use non-sparking tools.
- Take action to prevent static discharge.
- Do not breathe fumes, vapours or spray.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.
- Use personal protective equipment as required.

Precautions for Storage:

- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Store in the original container.
- Keep container tightly closed.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA ppm	mg/m³	STEL ppm	mg/m³
Naphthalene	[91-20-3]	0.5	2.6	2	10
Xylene (o-, m-, p-isomers)	[1330-20-7]	50	217	-	-
Ethyl benzene	[100-41-4]	20	88	40	176

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the

short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

Personal Protection Equipment:



Eyes	Safety glasses with side shields. Avoid wearing contact lenses.	
Hands	Wear chemical resistant gloves. Recommended material: Nitrile	
Body	Chemical/oil resistant clothing is recommended.	
Respiratory	Type A filter material (organic vapour)	
	Refer to AS/NZS 1715: Selection, Use and Maintenance of Respiratory	
	Equipment and AS/NZS 1716: Respiratory Protective Devices	
	for further details on the use of respiratory protective equipment.	

Section 9 Physical and Chemical Properties

A = = = = = = = = = = = = = = = = = = =	Liquid
Appearance	Liquid
Colour	Amber
Odour	Solvent
Odour Threshold	Not available
рН	Not available
Boiling Point	150°C for solvent
Melting Point	Not available
Freezing Point	Not available
Flash Point	32°C
Flammability	Flammable liquid or vapour
Lower to upper	Not available
Flammable Limits	
Volatile Component	Not available
Relative Vapour Density	Not available
Specific Gravity	0.920
Solubilities	Not available
Partition Coefficient:	Not available
Auto-ignition	Not available
Temperature	
Decomposition	Not available
Temperature	
Kinematic Viscosity	Not available
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance Stable under normal conditions of storage and handling.	
Conditions to Avoid	Heat, open flames, direct sunlight and other sources of ignition.
Incompatible Materials Strong oxidisers. Other flammable materials	
Hazardous Decomposition	No data available.
Products	

Section 11 Toxicological Information

Acute Effects:

Swallowed	May be fatal if swallowed and enters airways.	
Dermal	Not applicable.	

Inhalation	Not applicable.	
Eye	Causes serious eye irritation.	
Skin	Causes skin irritation. May cause an allergic skin reaction.	

Chronic Effects:

Carcinogenicity	Not applicable.	
Reproductive	Not applicable.	
Toxicity		
Germ Cell	Suspected of causing genetic defects.	
Mutagenicity		
Aspiration	Not applicable.	
STOT/SE	Not applicable.	
STOT/RE	May cause damage to organs through prolonged or repeated exposure	

Section 12. Ecotoxicological Information

Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable, Ecotoxic" and that the label also has the Flammable, Ecotoxic Pictogram, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: Avoid release to the environment.

Section 14

Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)



Road, Rail, Sea and Air Transport

UN No	1993	
Class - Primary	3	
Packing Group	III	
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.	
Marine Pollutant	Yes	
Special Provisions	If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.	

Section 15	Regulatory Information
------------	------------------------

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Schedule 6 Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Fire Extinguisher Quantities	500L – 2x required
Signage Trigger Quantities	1000L
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	Only use for the intended purpose.

Section 16	Other Information
Glossary	
Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms
	inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible
	authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

- 1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- 2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
- 3. Standard for the Uniform Scheduling of Medicines and Poisons.
- 4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 6. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 7. American Conference of Industrial Hygienists (ACGIH).
- 8. Globally Harmonised System of Classification and Labelling of chemicals.

New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).

- 4. Transport of Dangerous goods on land NZS 5433:2020
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 7 March 2023 Review Date: 7 March 2028