

# SAFETY DATA SHEET

## Section 1. Identification of the material and the supplier

Product: Weatherfast Pri-Coat

Item Code: 8200

Product Use: Enamel primer/undercoat for wood, non-ferrous metals,

and most other surfaces. Applied by brush, roller or spray.

Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**Address: 59 Moxon Road

Punchbowl NSW 2196

Australia

Telephone: +61 2 9708 2200 Email: info@norglass.com.au

New Zealand Supplier: xxx Address: xxx xxx

Telephone: 0508 724687

**Emergency Numbers:** 

Australia: 13 1126 (Poisons Information Centre)
New Zealand: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 15 November 2023

# Section 2. Hazards Identification

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

#### **New Zealand:**

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

# EPA Approval No: Surface Coatings and Colourants (Flammable, Carcinogenic) – HSR002669

#### **Pictograms**









Signal Word: DANGER

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.

Product Name: Weatherfast Pri-Coat SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Carcinogenicity Cat. 2	H351	Suspected of causing cancer.
Reproductive toxicity Cat. 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.

<b>Prevention Code</b>	Prevention Statement
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362 + P364	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

<b>Storage Code</b>	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

#### Section 3. **Composition / Information on Ingredients**

Ingredients	Wt%	CAS NUMBER.
Alkyd Resin	28-35%	Proprietary
Pigments and extenders various	45-50%	Proprietary
Low Odour Hydrocarbon Solvent	10-15%	Proprietary
Additives	Up to 100%	Proprietary

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz Product Name: Weatherfast Pri-Coat

Date of SDS: 15 November 2023

#### Section 4. First Aid Measures

## Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. If eye irritation persists:

Get medical advice.

If on Skin Wash with plenty of soap and water. If skin irritation or rash occurs: get

medical advice/attention.

If Swallowed Rinse mouth. DO NOT induce vomiting. If the victim is conscious give

water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult.

## Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Not applicable. **Inhalation:** Not applicable.

**Skin:** Causes skin irritation. May cause an allergic skin reaction.

**Eye:** Not applicable.

**Chronic:** May be fatal if swallowed and enters airways. May damage fertility or the

unborn child. May cause damage to organs through prolonged or repeated

exposure.

## **Section 5.** Fire Fighting Measures

Hazard Type	Flammable liquid vapours can explode in air if ignited.
Hazards from	None known.
combustion	
products	
Suitable	Extinguishing media carbon dioxide, foam or dry chemicals.
Extinguishing	
media	
<b>Precautions for</b>	Wear full body protection and self-contained breathing apparatus.
firefighters and	
special protective	
clothing	
HAZCHEM CODE	3Y

#### Section 6. Accidental Release Measures

#### **Personal precautions:**

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

#### **Environmental precautions:**

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

#### Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

#### Section 7. Handling and Storage

Product Name: Weatherfast Pri-Coat SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

#### **Precautions for Handling:**

- Read carefully and follow all instructions.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only outdoors or in a well-ventilated area.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective clothing and equipment.

## **Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- Keep out of reach of children.

# Section 8 Exposure Controls / Personal Protection

## **WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have known exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

### **Engineering Controls**

Use only in well ventilated areas. Introduce local exhaust ventilation if necessary.

## **Personal Protection Equipment**









Eyes	Wear safety goggles with side shields.	
Hands and	Wear neoprene rubber gloves. Wear overalls and use barrier cream.	
Skin		
Respiratory	Avoid breathing vapours or dust by wearing organic vapour respirator.	

# Section 9 Physical and Chemical Properties

Appearance	Off white viscous liquid
Odour	Solvent odour
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	150°C for solvent
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	32°C

Product Name: Weatherfast Pri-Coat SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Flammability	Not applicable
Upper and Lower	Not applicable
<b>Exposure Limits</b>	
<b>Volatile Component</b>	20%
Vapour Pressure 25°C	Not applicable
Specific Gravity	1.400 - 1.450
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition	Not applicable
Temperature	
Decomposition	Not applicable
Temperature	
<b>Kinematic Viscosity</b>	Not applicable
<b>Particle Characteristics</b>	Not applicable

# Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	None known.
<b>Hazardous Decomposition</b>	None known.
Products	

# Section 11 Toxicological Information

#### **Acute Effects:**

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Causes skin irritation. May cause an allergic skin reaction.

## **Chronic Effects:**

Carcinogenicity	Suspected of causing cancer.	
Reproductive	Suspected of damaging fertility or the unborn child.	
Toxicity		
Germ Cell	Not applicable.	
Mutagenicity		
Aspiration	May be fatal if swallowed and enters airways.	
STOT/SE	Not applicable.	
STOT/RE	Causes damage to organs through prolonged or repeated exposure.	

## **Section 12. Ecotoxicological Information**

Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

## **Section 13. Disposal Considerations**

**Disposal Method:** Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance

Product Name: Weatherfast Pri-Coat SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

with local regulations. Ensure container is sealed and isolated away from ignition sources.

**Precautions:** Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

**Disposal methods to avoid:** Do not allow to enter waterways.

## Section 14 Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2020



## Road, Rail, Sea and Air Transport

UN No	1263	
Class - Primary	3	
Packing Group	III	
<b>Proper Shipping Name</b>	e PAINT, FLAMMABLE LIQUID	
Marine Pollutant	YES	
<b>Special Provisions</b>	If the product's individual container is below 5L/kg, it can be	
	transported as a non-DG as long as the product packaging is still	
	labelled as per DG requirements and the driver is given safety	
	information in accordance with Chapter 3.4 of the UNRTDG.	

## Section 15 Regulatory Information

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### **New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Surface Coatings and Colourants (Flammable, Carcinogenic) - HSR002669

HSW (HS) Regulations 2017 and EPA	Trigger Quantity	
Notices		
Certified Handler	Not required	
Location Certificate	500L (>5L), 1500L(<5L), 250L open	
Tracking Trigger Quantities	Not required	
Signage Trigger Quantities	1000L	
Emergency Response Plan	1000L	
Secondary Containment	1000L	
Restriction of Use	Only use for the intended purpose.	

Section to Other Information	Section	16	Other :	Informatior
------------------------------	---------	----	---------	-------------

Glossary

EC<sub>50</sub> Median effective concentration.

Product Name: Weatherfast Pri-Coat SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

EEL Environmental Exposure Limit.
EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC<sub>50</sub> Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD<sub>50</sub> Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

#### References:

#### Australia:

- 1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- 2. Standard for the Uniform Scheduling of Medicines and Poisons.
- 3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 5. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 6. American Conference of Industrial Hygienists (ACGIH).
- 7. Globally Harmonised System of classification and labelling of chemicals.

#### New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2020
- 5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 15 November 2023 Review Date: 15 November 2028

Product Name: Weatherfast Pri-Coat
Date of SDS: 15 November 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz