

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Fax: 61 2 9796 3069

Email: norglass@bigpond.net.au

www.norglass.com.au



WEATHERFAST MARINE DECK PAINT

DESCRIPTION: A hard wearing polyurethane, low gloss, low-odour coating containing synthetic slip resistant particles.

USES: For traffic areas with intermittent water contact or damp areas such as boat decks paths, wooden decks, stairs and floors.

PROPERTIES (at 20°C)

COLOUR: 7 standard pastel shades
Shoreline Cream, Horizon Blue, Misty Grey, Arctic White, Seashell, Cream and Squall Grey, Arctic White can be blended with other colours to reduce the intensity.

TOXICITY: See precautions

FINISH: Low sheen

COVERAGE: Up to 10 sqm per litre, depending on surface and profile

DRYING TIME: Touch dry in 2 hours at 20°C and 50% relative humidity

RECOATING: After 16 hours

POT LIFE: N/A

MIXING RATIO: N/A

THINNING: Up to 5% Weatherfast Brushing Thinner in hot weather

WEIGHT/LITRE: 1.130 kg – 1.250 kg (depending on colour)

VOLUME SOLIDS: 50%

FLASH POINT: 32°C

CLEAN UP:	Weatherfast Brushing Thinner or Weatherfast Spraying Thinner
UN NUMBER:	1263
PREPARATION:	Prime bare timber with Norglass Pri-Coat and allow to dry, for other surfaces use Norglass Shipshape Primer Undercoat according to directions. For raw steel or aluminium use Metal etch Gel then prime with Shipshape. Unpainted concrete must be washed with Norglass Concrete & Ceramic Cleaner, hosed off and allowed to thoroughly dry before painting. Fibreglass should be sanded, cleaned with Norclean Plus and primed with Shipshape, where a textured area is to be painted, scrub down slip resistant surfaces with a domestic dishwashing liquid using warm water. Hose off thoroughly with fresh water and allow to dry, wipe over with Norclean Plus. Prime with Shipshape. Sand previously painted slip resistant surfaces with a 240 grit sandpaper, remove the dust and clean with Norclean plus. Sand off any unsound, flaking or powdery paint, clean with Norclean Plus before proceeding.
APPLICATION:	Stir thoroughly before use. Confine the use of a brush to perimeters only to avoid patchiness. Where possible mask out the area to be coated with blue masking tape. Use a short nap (4-6mm) nylon or mohair paint roller for best results and apply with even strokes. 2 coats recommended. Allow a minimum of 24 hours before permitting general traffic use.
TRANSPORTATION:	DG Class 3 HAZCHEM 3Y P.G. III Sizes available – 4litre, 1litre and 500ml. Commercial packs of 20litres also available.
PRECAUTIONS:	Provide adequate ventilation during use. Do not smoke or expose to naked flame. Wash hands thoroughly before eating or smoking. Do not spray this product unless special apparatus is used to accommodate the particle size.
FIRST AID:	If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 13 11 26 or (NZ) 0800 764 766 and have label information ready. If swallowed DO NOT induce vomiting. Give large quantities of water or milk. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and consult a doctor. Remove contact lenses if present and easy to do and continue rinsing. If skin contact causes irritation, remove contaminated clothing and wash skin thoroughly. If breathing difficulty arises remove to fresh air. Apply artificial respiration if not breathing.
SPECIAL INSTRUCTIONS:	Do not use below 10°C as drying will be inhibited and moisture entrapment will likely impair the finish. NOTE: Thorough stirring is essential before use due to the weight of the plastic granules (they tend to float), as they have to be dispersed into the film before applying.