

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **Paving Paint – Slip Resistant & Smooth**
 Item Code: 8130 and 8150
 UN No: 1263
 Product Use: Paint on Concrete, Fibrous Sheeting & Timber
 Air Dry Enamel applied by brush roller or spray, in accordance with product data sheet.

Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**
 Address: 59 Moxon Road
 Punchbowl NSW 2196
 Australia
 Telephone: +61 2 9708 2200
 Email: techinfo@norglass.com.au

New Zealand Supplier: xxx
 Address: xxx
 Telephone: 0508 724687

Emergency Numbers:
Australia: 13 1126 (Poisons Information Centre)
New Zealand: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 10 December 2023 v3

Section 2. Hazards Identification

Australia:
 Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:
 This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

Surface Coatings and Colourants (Flammable, Carcinogenic) – HSR002669

Pictograms



Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.

Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Carcinogenicity Cat. 2	H351	Suspected of causing cancer.
Specific target organ toxicity – repeated exposure Cat. 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take action to prevent static discharge.
P261	Avoid breathing fumes or vapours.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362 + P364	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, foam for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Urethane Alkyd Resin	40-45	Proprietary

Product Name: Paving Paint
Date of SDS: 10 December 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Pigments	30-35	Proprietary
White Spirits	12-15	64742-88-7
Additives various	<5%	Proprietary

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	May be fatal if swallowed and enters airways.
Inhalation:	Not applicable.
Skin:	Causes skin irritation. May cause an allergic skin reaction.
Eye:	Causes serious eye irritation.
Chronic:	Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Section 5. Fire Fighting Measures

Hazard Type	Flammable liquid and vapours can explode if ignited.
Hazards from combustion products	Burning may produce carbon monoxide and carbon dioxide.
Suitable Extinguishing media	Foam, carbon dioxide or dry chemicals.
Precautions for firefighters and special protective clothing	Wear full body protection and self-contained breathing apparatus.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Personal precautions:

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

Section 7. Handling and Storage

Precautions for Handling:

- Read carefully and follow all instructions.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing fumes or vapours.
- Keep container tightly closed.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing.
- Use personal protective equipment as required.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- Keep out of reach of children.
- Do not obliterate label instructions on partly used containers.
- Partly used containers should be properly sealed to avoid spillage.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
White Spirit	150	790		

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

Local exhaust ventilation is usually required. Provide explosion proof ventilation system.

Personal Protection Equipment:



Eyes	Wear safety goggles with side shields.
Hands and Skin	Wear neoprene rubber gloves. Wear overalls and use barrier cream.
Respiratory	Avoid breathing solvent vapours by wearing organic vapour respirators.

Section 9**Physical and Chemical Properties**

Appearance	White or coloured viscous liquid
Odour	Low solvent odour
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	150°C for solvent
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	32°C
Flammability	Not applicable
Upper and Lower Exposure Limits	Not applicable
Volatile Component	Not available
Vapour Pressure 25°C	Not applicable
Specific Gravity	1.120 – 1.220
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	None known.
Hazardous Decomposition Products	None known.

Section 11**Toxicological Information****Acute Effects:**

Swallowed	Not triggered but if swallowed may cause irritation of mouth, throat and digestive system, resulting in nausea and vomiting.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes severe eye irritation.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.
Reproductive Toxicity	Not applicable
Germ Cell Mutagenicity	Not applicable.
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Causes damage to organs through repeated or prolonged exposure. Avoid prolonged exposure to solvent vapours.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

Disposal methods to avoid: Do not allow to enter waterways.

Section 14 Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020



Road, Rail, Sea and Air Transport

UN No	1263
Class - Primary	3
Packing Group	III
Proper Shipping Name	PAINT
Marine Pollutant	YES
Special Provisions	If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

NOT Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Surface Coatings and Colourants (Flammable, Carcinogenic) – HSR002669

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
--	-------------------------

Product Name: Paving Paint
Date of SDS: 10 December 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 10 December 2023

Review Date: 10 December 2028

Product Name: Paving Paint

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 10 December 2023

Tel: 64 9 475 5240

www.techcomp.co.nz