

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200

Email: reception@norglass.com.au

norglass.com.au



PAVING PAINT BARRIER UNDERCOAT

DESCRIPTION: A single pack, clear, thermoplastic resin with superior sealing and adhesion properties.

USES: PAVING PAINT BARRIER UNDERCOAT is designed to seal off and stabilise surfaces previously coated in an unknown product, prior to using Norglass PAVING PAINT.

PROPERTIES (at 20°C)

COLOUR: Clear

TOXICITY: See precautions

COVERAGE: 10 Sqm per litre

DRYING TIME: Product will be touch dry in 60-90 minutes at 25°C and 50% relative humidity. In cooler temperatures the drying time may be slightly extended. BARRIER UNDERCOAT should be overcoated within a few hours of application. Do not leave longer than 4 hours.

RECOATING: Only one coat of Barrier Undercoat is required. Must be overcoated with Norglass Paving Paint.

POT LIFE: N/A

THINNING: This product does not require thinning prior to application.

WEIGHT/LITRE: 0.820

VOLUME SOLIDS: 22%

FLASH POINT: 72°C

CLEAN UP: Use WEATHERFAST BRUSHING THINNERS.

U.N. NUMBER: 3295

- PREPARATION:** The surface must be thoroughly cleaned using a high-pressure hose system to ensure any dirt, grease, oil or other contaminants are removed prior to application. Flaking or chalking paint must also be removed. Patches of bare concrete that remain must be cleaned using NORGLASS CONCRETE CLEANER. The surface must be completely dry before applying BARRIER UNDERCOAT as any moisture present may lead to adhesion problems.
- APPLICATION:** Product must be thoroughly mixed prior to application. **Only one coat is required.** Apply using a Short Nap (4-8mm) Microfibre/Mohair roller cover. Confine the use of a Brush to the edges. Roll out the product evenly across the surface not allowing it to pool in any pitting concrete. Note: This product cannot be sprayed.
- TRANSPORTATION:** DG Class 3 HAZCHEM 3YE P.G. III
Sizes available: 10litre, 4litre, 1litre.
- PRECAUTIONS:** Wear gloves and goggles when using. Provide adequate ventilation during use. Do not smoke and keep away from naked flames.
- FIRST AID:** If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 13 11 26 or (NZ) 0800 764 766 and have label information ready.
If swallowed DO NOT induce vomiting. Give large quantities of water or milk. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and consult a doctor. Remove contact lenses if present and easy to do and continue rinsing. If skin contact causes irritation, remove contaminated clothing and wash skin thoroughly. If breathing difficulty arises remove to fresh air. Apply artificial respiration if not breathing.
- SPECIAL INSTRUCTIONS:** This coating is NOT designed to be a finish coat, and must be overcoated with NORGLASS PAVING PAINT.

Although this coating is designed to seal over old paint systems (i.e Xylene or water based coatings), it is not intended to fix previously failed paint systems. Areas that show large signs of failure, e.g. delamination, Norglass recommends you have the surface professionally ground back to raw concrete and then paint as normal.

PREPARATION AND APPLICATION FOR NORGLASS PAVING PAINT:

Ensure NORGLASS BARRIER UNDERCOAT is touch dry (after the required 60-90 mins) before the first coat of NORGLASS PAVING PAINT is applied. **It is important that all footwear is dry and clean from any form of contamination before walking on the undercoated surface.** Apply NORGLASS PAVING PAINT as per the instructions on the can. Please note the gradient (slope) advice for using PAVING PAINT before using this product as an undercoat.